

THREE-AXLE AGRICULTURAL TRAILER GT SERIES

This three-axle trailer is suitable for transporting both self-propelled agricultural machinery..

The platform is equipped with loading ramps, so as to enable easy loading and unloading of self-propelled machinery.

Chassis: The chassis is made up of two H-section beams and two UPN-section side beams, together connected through crossmembers, electrically welded.

Axles: three heavy-duty axles with extra-large cast-iron drum brakes (11 13/16 inches diameter, 5 1/2 inches width) with riveted friction lines and adjustable levers.

Suspensions: leaf springs with an eye and a flat end, for front axle, and cantilever leaf springs, for rear axles.

Braking: hydraulic, semi-continuous and automatic braking or pneumatic, semi-continuous and automatic braking (see table below).

Load transfer (patented): load transfer device to transfer a certain amount of the total trailer weight to the tractor hook, in order to get a higher degree of stability by braking and a better climb capacity on the hilly roads.

Painting: anti rust primer and two coats of synthetic paint.

types

Code	Type	Platform Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In italy) [kg.]	Empty weight [kg.]	Braking	Suspensios	Platform height from the ground {·} [m]	Dual wheels
00150.R	GT 200	6.60x2.50	26000	20000	5400	hydraulic, semi-continuous and automatic	with leaf springs	0.68÷1.02	215/75 R 17.5 new
00154.R	GT 200 P	6.60x2.50	26000	20000	5400	pneumatic, semi-continuous and automatic	with leaf springs	0.68÷1.02	215/75 R 17.5 new

{·} Platform height is measured with standard tires and with laden trailer.

optional equipment

Optional equipment upon request	
Code	Description
00320.A	Hydraulic semi-continuous and automatic braking system, to be mounted on the tractor unit
00322.A	Trailer hitch, category D2 (according to CUNA, the Italian automotive standardization body)
00324.A	Trailer hitch, category D3 (according to CUNA, the Italian automotive standardization body)
00334.A	Hydraulic loading ramps for GT 200 – GT 200 P
00336.A	Side panels H=0,50 m for GT 200 – GT 200 P
00338.A	Hydraulic rear stabilizer jacks for GT 200 – GT 200 P

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.