

DUAL PURPOSE SINGLE AXLE AGRICULTURAL TRAILER MU SERIES

This single axle trailer is suitable for transporting both loose goods and self-propelled agricultural machinery.

It is equipped with a double tilting system, namely one system enabling three-way 45° tipping of the body with a view to unloading loose material, and the other one enabling rear tilting of the body until it reaches a 10°÷12° approach angle, with a view to loading and unloading self-propelled machinery by means of the tailgate ramp.

Chassis: The chassis is made up of two UPN longitudinal members, which are held together by C-section and UPN-section crossmembers and also by one closed-section crossmember.

Body: The platform is made of checker plate and is equipped with sideboards. The body's robust structure is made up of two UPN longitudinal members which are held together by closed-section and C-section stiffening crossmembers. On MU 90 types the sideboards are equipped with removable center posts.

Braking: hydraulic and semi-continuous braking or pneumatic, semi-continuous and automatic braking (see table below).

Suspensions: stiff or with parabolic leaf springs with an eye and a flat end, depending on the type (see table below).

Painting: anti rust primer and two coats of synthetic paint.

types

Code	Type	Body Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In Italy) [kg.]	Empty weight [kg.]	Braking	Suspensions	Platform height from the ground {·} [m]	Dual wheels
00124.R	MU 80 °°	4.07x2.20x0.50	8000	6000	1900	hydraulic and semi-continuous	stiff	83	225/75 R 17.5 used
00124.R1	MU 80 P °°	4.07x2.20x0.50	8000	6000	1900	pneumatic, semi-continuous and automatic	stiff	83	225/75 R 17.5 used
00125.R	MU 80	4.07x2.20x0.50	10000	6000	1900	hydraulic and semi-continuous	stiff	83	215/75 R 17.5 new
00125.R2	MU 80 P	4.07x2.20x0.50	10000	6000	1900	pneumatic, semi-continuous and automatic	stiff	83	215/75 R 17.5 new
00125.R1	MU 80 A	4.07x2.20x0.50	10000	6000	1900	hydraulic and semi-continuous	with leaf springs	83	215/75 R 17.5 new
00125.R3	MU 80 A P	4.07x2.20x0.50	10000	6000	1900	pneumatic, semi-continuous and automatic	with leaf springs	83	215/75 R 17.5 new
00127.R	MU 90 °°	5.07x2.40x0.50	8000	6000	2380	hydraulic and semi-continuous	stiff	86	225/75 R 17.5 used
00127.R1	MU 90 P °°	5.07x2.40x0.50	8000	6000	2380	pneumatic, semi-continuous and automatic	stiff	86	225/75 R 17.5 used
00128.R	MU 90	5.07x2.40x0.50	10000	6000	2380	hydraulic and semi-continuous	stiff	86	215/75 R 17.5 new
00128.R2	MU 90 P	5.07x2.40x0.50	10000	6000	2380	pneumatic, semi-continuous and automatic	stiff	86	215/75 R 17.5 new
00128.R1	MU 90 A	5.07x2.40x0.50	10000	6000	2380	hydraulic and semi-continuous	with leaf springs	86	215/75 R 17.5 new
00128.R3	MU 90 A P	5.07x2.40x0.50	10000	6000	2380	pneumatic, semi-continuous and automatic	with leaf springs	86	215/75 R 17.5 new

{·} Platform height is measured with standard tires. On trailers with leaf spring suspensions it is measured when the trailer is laden.

optional equipment

Optional equipment upon request	
Code	Description
00268.A2	Up- und downward-opening sideboards for NSR 60/70/80 - MU 80
00268.A3	Up- und downward-opening sideboards for NSR 90/100 - MU 90 - MU 90 A -MU 140 - MU 140 P
00283.A7	Automatic hydraulic braking, for MU 80 °° - MU 80 – MU 80 A
00283.A8	Automatic hydraulic braking, for MU 90 °° - MU 90 – MU 90 A
00316.A	Protection frame for bale transport
00325.A	Additional charge for new 235/75R17.5 tires for types MU80/90 (the additional charge is to be added to the price of the trailer with new 215/75R17.5 tires)
00332.A	Hydraulic jack for MU 80/80A - MU 90/90A
00342.A	Side panel extensions H=0.50 m for MU 80 - MU 80 A
00346.A	Side panel extensions H=0.50 m for MU 90 - MU 90 A

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzzi Co. in order to offer to the customers a product with increased quality and performance.