

## SINGLE DRIVE AXLE AGRICULTURAL TIPPING TRAILER NSR TM - PM SERIES

This agricultural trailer with drive axle is equipped with a three-way tipping and a rear tilting mechanism. It is especially designed to transport loose goods.

**Chassis:** The chassis is made up of two U-section (UPN) longitudinal members, which are held together by 4 electro-welded U-section (UPN) crossmembers.

**Body:** The platform is made of checker plate and is equipped with sideboards. The up- and downward-opening tailgate is supplied as standard equipment.

The body's robust structure is made up of two U-section (UPN) longitudinal members which are held together by U-section and rectangular hollow section stiffening crossmembers.

**Braking:** mechanical or hydraulic depending on the type (see table below).

**Suspensions:** stiff

**Painting:** anti rust primer and two coats of synthetic paint.

### types

Code	Type	Body Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In Italy) [kg.]	Empty weight [kg.]	Braking	Platform height {•} [m]	Tilting	Wheels
00040.R	NSR 40 P M	2.70x1.70x0.40	3500	3500	1060	mechanical	0.90	rear	single 10.0/75 -15.3 14 PR, new
00076.R	NSR 40 T M	2.70x1.70x0.40	3500	3500	1060	mechanical	0.90	three-way	single 10.0/75 -15.3 14 PR, new
00042.R	NSR 50 P M	3.00x1.80x0.50	4500	4500	1160	mechanical	0.92	rear	single 10.0/75 -15.3 14 PR, new
00078.R	NSR 50 T M	3.00x1.80x0.50	4500	4500	1160	mechanical	0.92	three-way	single 10.0/75 -15.3 14 PR, new
00044.R	NSR 60 P M	3.50x2.00x0.50	6000 (*)	5000	1460	mechanical	0.98	rear	single 11.5/80 -15.3 14 PR, new
00080.R	NSR 60 T M	3.50x2.00x0.50	6000 (*)	5000	1460	mechanical	0.98	three-way	single 11.5/80 -15.3 14 PR, new
00046.R	NSR 70 P M	4.00x2.20x0.60	8000	5000	1860	hydraulic	1.02	rear	dual 245/70R19.5, used
00082.R	NSR 70 T M	4.00x2.20x0.60	8000	5000	1920	hydraulic	1.02	three-way	dual 245/70R19.5, used
00048.R	NSR 80 P M	4.00x2.20x0.60	8000	6000	1860	hydraulic	1.02	rear	dual 245/70R19.5, used
00084.R	NSR 80 T M	4.00x2.20x0.60	8000	6000	1920	hydraulic	1.02	three-way	dual 245/70R19.5, used

{•} Platform height is measured with standard tires.

(\*) The technically permissible load can only be guaranteed when the trailers have the optional tires marked with (°) in the optional equipment table on.

## optional equipment

Optional equipment upon request	
Code	Description
00262.A	Side panel extensions H=0.40 m for NSR 40 T/P - NSR 40 T/P M
00263.A	Side panel extensions H=0.50 m for NSR 50 T/P - NSR 50 T/P M
00264.A	Side panel extensions H=0.50 m for NSR 60 T/P - NSR 60 T/P M
00266.A	Side panel extensions H=0.60 m for NSR 70 T/P - NSR 80 T/P - NSR 70 T/P M
00268.A1	Up- und downward-opening sideboards for NSR 40 T - NSR 50 T - NSR 40 T M - NSR 50 T M
00268.A2	Up- und downward-opening sideboards for NSR 60 T - NSR 70 T - NSR 80 T - MU 80 - NSR 60 T M - NSR 70 T M - NSR 80 T M
00270.A	Grain chute
00280.A1	Additional charge for new 7.50-16 14 P.R. dual tires for types NSR 60 T/P M (°)
00282.A6	Hydraulic braking (internal reference only) for NSR 40 T/P M
00282.A7	Hydraulic braking (internal reference only) for NSR 50 T/P M
00282.A8	Hydraulic braking (internal reference only) for NSR 60 T/P M
00284.A2	Protection frame for bale transport on TL 25-30-35 - NSR 40 T/P- NSR 40 T/P M H= 1.10 m
00284.A3	Protection frame for bale transport on NSR 50 T/P - NSR 50 T/P M H= 1.10 m
00284.A4	Protection frame for bale transport on NSR 60 T/P- NSR 60 T/P M H= 1.20 m
00284.A5	Protection frame for bale transport on NSR 70 T/P - 80 T/P- NSR 70 T/P M H= 1.40 m
00286.A	Additional winch
The side panel extensions must be ordered together with the trailer, because center posts and hinges are not supplied if no side panel extensions are ordered.	
Tyres: see art. 7 of the general terms and conditions for sale and use	

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.