

## FLATBED TRAILER FOR THE TRANSPORT OF CUTTER BARS PB SERIES

This flatbed trailer is especially designed to transport cutter bars for combine harvesters. Thanks to its telescopic drawbar, adjustable cutter bar support brackets and height-adjustable hitch unit, it can be easily towed by all types of combine harvester.

This vehicle is registered both as trailed agricultural machine (low loader) PB 25 and as agricultural trailer PB 25 R, which means that the former can be towed by a combine harvester, while the latter can be towed by a farm tractor.

**Chassis:** The chassis is made up of a hot-rolled rectangular hollow section that contains the likewise hot-rolled telescopic drawbar. The cutter bar support brackets, which can be adjusted in longitudinal and transverse direction, are secured to the longitudinal members.

**Parking brake:** mechanical.

**Suspensions:** stiff.

**Painting:** anti rust primer and two coats of synthetic paint.

### types

Code	Type	Maximum Dimensions [m]	Maximum cutter bar dimensions [kg.]	Technically permissible load [kg.]	Maximum authorised load (in italy) [kg]	Empty weight [kg.]	Parking brake	Vehicle classification	Towable exclusively by	Single wheels
00162.R	<b>PB 25</b>	9.875x2.25	6.00	2500	2500	516	mechanical	trailed agricultural machine	combine harvester	6.00-9 10 P.R. new
00164.R	<b>PB 25 R</b>	9.875x2.25	6.00	2500	2500	516	mechanical	trailer	agricultural tractor	6.00-9 10 P.R. new

### optional equipment

Optional equipment upon request	
Code	Description
00400.A	Spare wheel+spare wheel carrier for PB 25 - PB 25 R
00402.A	Additional charge for new 6.00-9 12 P.R. single tires for PB 25 – PB 25 R

*The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.*