

## SINGLE AXLE AGRICULTURAL TRAILER PT SERIES

This single axle agricultural trailer is suitable for the transport of self-propelled agricultural machinery.

The platform can be tilted backwards, so as to enable easy loading and unloading of self-propelled machinery.

**Chassis:** The chassis is made up of four U-section (UPN) longitudinal members that are held together by electro-welded crossmembers and connection heads.

**Braking:** mechanical or hydraulic and semi-continuous depending on the type (see table below).

**Suspensions:** stiff.

**Painting:** anti rust primer and two coats of synthetic paint.

### types

Code	Type	Platform Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In Italy) [kg.]	Empty weight [kg.]	Braking	Maximum external width [m]	Platform height from the ground {•} [m]	Wheels
00100.R	PT 36	3.50x1.52	4500	3600	730	mechanical	2.085	0.51	215/75 R17.5 new
00100.R1	PT 36 °°	3.50x1.52	4500	3600	730	mechanical	2.085	0.51	235/75 R 17.5 used
00101.R	PT 36 L	4.50x1.52	5000	5000	910	mechanical	2.085	0.53	215/75 R17.5 new
00101.R1	PT 36 L °°	4.50x1.52	5000	5000	910	mechanical	2.085	0.53	235/75 R 17.5 used
00102.R	PT 40	3.50x1.76	5000	4000	780	mechanical	2.32	0.53	215/75 R17.5 new
00102.R2	PT 40 °°	3.50x1.76	5000	4000	780	mechanical	2.32	0.53	235/75 R 17.5 used
00103.R	PT 40 L	4.50x1.76	5000	5000	970	mechanical	2.32	0.53	215/75 R17.5 new
00103.R1	PT 40 L °°	4.50x1.76	5000	5000	970	mechanical	2.32	0.53	235/75 R 17.5 used
00104.R	PT 50	4.00x1.89	5000	5000	980	mechanical	2.45	0.53	215/75 R17.5 new
00104.R1	PT 50 °°	4.00x1.89	5000	5000	980	mechanical	2.45	0.53	235/75 R 17.5 used
00105.R	PT 50 L	4.50x1.89	5000	5000	1100	mechanical	2.45	0.53	215/75 R17.5 new
00105.R1	PT 50 L °°	4.50x1.89	5000	5000	1100	mechanical	2.45	0.53	235/75 R 17.5 used
00106.R	PT 60	4.00x1.94	6000	6000	1100	hydraulic and semi-continuous	2.50	0.55	235/75 R17.5 new
00106.R1	PT 60 °°	4.00x1.94	6000	6000	1100	hydraulic and semi-continuous	2.50	0.55	235/75 R 17.5 used
00107.R	PT 60 L	4.50x1.94	6000	6000	1220	hydraulic and semi-continuous	2.50	0.55	235/75 R17.5 new
00107.R1	PT 60 L °°	4.50x1.94	6000	6000	1220	hydraulic and semi-continuous	2.50	0.55	235/75 R 17.5 used

{•} Platform height is measured with standard tires.

## optional equipment

Optional equipment upon request	
Code	Description
00282.A10	Hydraulic braking with drum 300x60 (internal reference only) for PT 36 -PT 40
00282.A11	Hydraulic braking with drum 300x60 (internal reference only) for PT 50
00282.A16	Hydraulic braking with drum 300x60 (internal reference only) for PT 36 L – PT 40 L
00282.A17	Hydraulic braking with drum 300x60 (internal reference only) for PT 50 L
00283.A3	Automatic hydraulic braking, for PT 60 – PT 60 °° - PT 60 L – PT 60 L °°
00284.A8	Protection frame for bale transport on PT 40 – PT 40 L H=1.50 m
00284.A9	Protection frame for bale transport on PT 50 – PT 50 L H=1.50 m
00284.A10	Protection frame for bale transport on PT 60 – PT 60 L H=1.50 m
00286.A	Additional winch
00301.A	Mudguard for PT series
00304.A	Detachable sideboards for PT 36 – PT 40
00305.A	Detachable sideboards for PT 50 – PT 60
00317.A	Additional charge for new 235/75R17.5 tires for PT36/PT 36L–PT40/PT40L–PT50/PT50L. (the additional charge is to be added to the price of the trailer with new 215/75R17.5 tires)

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.