

SINGLE AXLE AGRICULTURAL TRAILER RB 100 SERIES

This single axle agricultural trailer is suitable for the transport of self-propelled agricultural machinery and bales.

The platform can be tilted backwards and is equipped with loading ramps, so as to enable easy loading and unloading of self-propelled machinery.

Chassis: The chassis is made up of two ILS longitudinal members that are held together by electro-welded crossmembers and connection heads.

Braking: hydraulic and semi-continuous braking or pneumatic, semi-continuous and automatic braking (see table below).

Suspensions: stiff or with parabolic leaf springs with an eye and a flat end, depending on the type (see table below).

Painting: anti rust primer and two coats of synthetic paint.

types

Code	Type	Platform/Body Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In Italy) [kg.]	Empty weight [kg.]	Braking	Suspensions	Platform height from the ground {·} [m]	Dual wheels
00116.R	RB 100	5.00x2.30	12000	6000	1850	hydraulic and semi-continuous	stiff	0.82	215/75 R 17.5 new
00117.R	RB 100 P	5.00x2.30	12000	6000	1850	pneumatic, semi-continuous and automatic	stiff	0.82	215/75 R 17.5 new
00118.R	RB 100 A	5.00x2.30	12000	6000	1850	hydraulic and semi-continuous	with leaf springs	0.82	215/75 R 17.5 new
00119.R	RB 100 A P	5.00x2.30	12000	6000	1850	pneumatic, semi-continuous and automatic	with leaf springs	0.82	215/75 R 17.5 new
00120.R	RB 100 C	5.00x2.30x0.50	12000	6000	1970	hydraulic and semi-continuous	stiff	0.82	215/75 R 17.5 new
00121.R	RB 100 C P	5.00x2.30x0.50	12000	6000	1970	pneumatic, semi-continuous and automatic	stiff	0.82	215/75 R 17.5 new
00122.R	RB 100 CA	5.00x2.30x0.50	12000	6000	1970	hydraulic and semi-continuous	with leaf springs	0.82	215/75 R 17.5 new
00122.R1	RB 100CAP	5.00x2.30x0.50	12000	6000	1970	pneumatic, semi-continuous and automatic	with leaf springs	0.82	215/75 R 17.5 new

{·} Platform height is measured with standard tires. On trailers with leaf spring suspensions it is measured when the trailer is laden.

 **optional equipment**

Optional equipment upon request	
Code	Description
00283.A6	Automatic hydraulic braking for RB 100
00286.A	Additional winch
00316.A	Protection frame for bale transport
00318.A	Side panel extensions H=0.50 m for RB 100 C - RB 100 CA
00332.A	Hydraulic jack RB 70/70L/80/100
00325.A	Additional price for new 235/75 R17.5 tires for RB70/70L/80/100 (the additional charge is to be added to the price of the trailer with new 215/75 R17.5 tires)

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.