

SINGLE AXLE AGRICULTURAL TRAILER RB 50 SERIES

This single axle agricultural trailer is suitable for the transport of self-propelled agricultural machinery.

The platform can be tilted backwards and is equipped with loading ramps, so as to enable loading and unloading of self-propelled machinery.

Chassis: The chassis is made up of two U-section (UPN) longitudinal members that are held together by electro-welded crossmembers and connection heads.

Braking: mechanical

Suspensions: stiff

Painting: anti rust primer and two coats of synthetic paint.

types

Code	Type	Platform Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In italy) [kg.]	Empty weight [kg.]	Braking	Suspensions	Platform height from the ground {·} [m]	Dual wheels
00108.R	RB 50 SS	4.00x2.10	7000	5000	1320	mechanical	stiff	0.83	215/75 R 17.5 new
00110.R	RB 50	4.00x2.10x0.50	7000	5000	1440	mechanical	stiff	0.83	215/75 R 17.5 new

{·} Platform height is measured with standard tires.

optional equipment

Optional equipment upon request	
Code	Description
00282.A12	Hydraulic braking with drum 300x60 (internal reference only) for RB 50 SS - RB 50
00284.A7	Protection frame for bale transport for RB 50 SS - RB 50 H=1.40 m
00286.A	Additional winch
00302.A	Side panel extensions for RB 50
00306.A	Detachable rear ramp carrier (to store the ramps in horizontal position) for RB 50 SS - RB 50 (internal reference only)
00308.A	Rear trailer hitch for RB 50 SS - RB 50 (internal reference only)

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.