

## SINGLE AXLE AGRICULTURAL TRAILER RB 70 - RB 70 L - RB 80 SERIES

This single axle trailer is suitable for transporting both self-propelled agricultural machinery and bales.

The platform can be tilted backwards and is equipped with a loading ramp, so as to enable easy loading and unloading of self-propelled machinery.

**Chassis:** The chassis is made up of two UPN longitudinal members (on types RB 70) or of two ILS longitudinal members (on types RB70 L and RB 80). The longitudinal members are held together by electro-welded stiffening crossmembers and connection heads.

**Braking:** hydraulic and semi-continuous braking or pneumatic, semi-continuous and automatic braking (see table below).

**Suspensions:** stiff; upon request parabolic leaf springs with an eye and a flat end are available for types RB 80.

**Painting:** anti rust primer and two coats of synthetic paint.

### types

Code	Type	Platform Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In italy) [kg.]	Empty weight [kg.]	Braking	Suspensions	Platform height from the ground {·} [m]	Dual wheels
00112.R	<b>RB 70</b>	4.80x2.40	8000	5000	1610	mechanical	stiff	0.84	215/75 R 17.5 new
00112.R1	<b>RB 70 °°</b>	4.80x2.40	8000	5000	1610	mechanical	stiff	0.84	225/75 R 17.5 used
00114.R	<b>RB 70 L</b>	6.00x2.40	9000	5000	1850	mechanical	stiff	0.84	215/75 R 17.5 new
00114.R1	<b>RB 70 L °°</b>	6.00x2.40	9000	5000	1850	mechanical	stiff	0.84	225/75 R 17.5 used
00115.R	<b>RB 80</b>	6.00x2.40	9000	6000	1850	hydraulic and semi-continuous	stiff	0.84	215/75 R 17.5 new
00115.R2	<b>RB 80 P</b>	6.00x2.40	9000	6000	1850	pneumatic, semi-continuous and automatic	stiff	0.84	215/75 R 17.5 new
00115.R1	<b>RB 80 °°</b>	6.00x2.40	9000	6000	1850	hydraulic and semi-continuous	stiff	0.84	225/75 R 17.5 used
00115.R3	<b>RB 80 P °°</b>	6.00x2.40	9000	6000	1850	pneumatic, semi-continuous and automatic	stiff	0.84	225/75 R 17.5 used

{·} Platform height is measured with standard tires. For trailers with leaf spring suspensions it is measured when the trailer is laden.

## optional equipment

Optional equipment upon request	
Code	Description
00282.A13	Hydraulic braking with drum 300x60 (internal reference only) for RB 70
00282.A14	Hydraulic braking with drum 300x60 (internal reference only) for RB 70 L
00283.A5	Automatic hydraulic braking, for RB 80 – RB 80 °°
00286.A	Additional winch
00315.A	Additional price for leaf springs on RB 80 – RB 80 P – RB 80 °° - RB 80 P °°
00316.A	Protection frame for bale transport
00319.A	Side panels H=0,50 m with center post for RB 70 L - RB 80
00323.A	Side panels H=0,50 m with center post for RB 70
00332.A	Hydraulic jack for RB 70/70L/80/80P
00325.A	Additional price for new 235/75 R17.5 tires for RB70/70L/80/80P (the additional charge is to be added to the price of the trailer with new 215/75 R17.5 tires)
00329.A	Removable guide rails at a distance of 2.50-2.55 m from each other on types RB 70/70L/80/80P

*The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.*