SINGLE AXLE AGRICULTURAL TRAILER TL SERIES

This single axle agricultural trailer is equipped with mechanical rear tipping gear. **Chassis**: The chassis is made up of two UPN or rectangular section longitudinal members that are held together by electro-welded crossmembers. **Body**: The platform is made of checker plate and is equipped with sideboards. **Braking**: mechanical. **Suspensions**: stiff.

Painting: anti rust primer and two coats of synthetic paint.

types

Code	Туре	Body Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In italy) [kg.]	Empty weight [kg.]	Braking	Platform height from the ground {*} [m]	Mechanical tilting	Single wheels
00003.R	TL 15	2.20x1.50x0.40	2000	1500	370	mechanical	0.70	rear	205/70 R 15
00004.R	TL 20	2.20x1.50x0.40	2000	2000	370	mechanical	0.70	rear	205/70 R 15
00005.R	TL 25	2.70x1.70x0.40	3500	2500	555	mechanical	0.81	rear	10.0/75 - 15.3 10 P.R.
00006.R	TL 30	2.70x1.70x0.40	3500	3500	555	mechanical	0.81	rear	10.0/75 - 15.3 10 P.R.
00007.R	TL 35	2.70x1.70x0.40	3500	3500	555	mechanical	0.81	rear	10.0/75 - 15.3 10 P.R.
{•} Platform height is measured with standard tires.									

optional equipment

Optional equipment upon request					
Code	Description				
00284.A1	Protection frame for bale transport on TL 15-20 - NSR 15 T/P – 20 T/P H= 1.00 m				
00284.A2	Protection frame for bale transport on TL 25-30-35 - NSR 40 T/P- NSR 40 T/P M H= 1.10 m				
00286.A	Additional winch				

The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzza Co. in order to offer to the customers a product with increased quality and performance.